

Victaulic® Auxiliary Drain Ball Valve Series ABV



30.76



1.0 PRODUCT DESCRIPTION

Available Sizes

- 1" Male NPT inlet x Female NPT outlet (with 1" plug)

Maximum Working Pressure

- 300psi/2056 kPa/20 bar

Application

- Utilized for a low point auxiliary drain valve or for drum drip connections for dry pipe systems

2.0 CERTIFICATION/LISTINGS

3.0 SPECIFICATIONS – MATERIAL

Valve body: Brass (with chrome-plated brass ball and Teflon™ seat)


Plug: Brass (with Teflon™ tape made-in)

Stem: Brass

Handle: Steel (handle sleeve is red gloss PVC with white “Aux. Drain” lettering)

4.0 DIMENSIONS

Series ABV



Size		Dimensions - Manual Handle				Weight
Nominal inches DN	Actual Outside Diameter inches mm	E to E inches mm	A inches mm	B inches mm	C inches mm	Approximate (Each) lb kg
1	1.315	4.25	7.00	2.50	4.75	1.3
DN25	33.7	108	178	64	121	0.6

ALWAYS REFER TO ANY NOTIFICATIONS AT THE END OF THIS DOCUMENT REGARDING PRODUCT INSTALLATION, MAINTENANCE OR SUPPORT.








5.0 PERFORMANCE

Series ABV

Size		Maximum Working Pressure
Nominal inches DN	Actual Outside Diameter inches mm	
1	1.315	300
DN25	33.7	2068

6.0 NOTIFICATIONS

⚠ WARNING

- Read and understand all instructions before attempting to install, remove, adjust, or maintain any Victaulic piping products.
- Depressurize and drain the piping system before attempting to install, remove, adjust, or maintain any Victaulic piping products.
- Wear safety glasses, hardhat, and foot protection.

Failure to follow these instructions could result in death or serious personal injury and property damage.

7.0 REFERENCE MATERIALS

[I-100: Field Installation Handbook](#)

User Responsibility for Product Selection and Suitability

Each user bears final responsibility for making a determination as to the suitability of Victaulic products for a particular end-use application, in accordance with industry standards and project specifications, as well as Victaulic performance, maintenance, safety, and warning instructions. Nothing in this or any other document, nor any verbal recommendation, advice, or opinion from any Victaulic employee, shall be deemed to alter, vary, supersede, or waive any provision of Victaulic Company's standard conditions of sale, installation guide, or this disclaimer.

Intellectual Property Rights

No statement contained herein concerning a possible or suggested use of any material, product, service, or design is intended, or should be construed, to grant any license under any patent or other intellectual property right of Victaulic or any of its subsidiaries or affiliates covering such use or design, or as a recommendation for the use of such material, product, service, or design in the infringement of any patent or other intellectual property right. The terms "Patented" or "Patent Pending" refer to design or utility patents or patent applications for articles and/or methods of use in the United States and/or other countries.

Note

This product shall be manufactured by Victaulic or to Victaulic specifications. All products to be installed in accordance with current Victaulic installation/assembly instructions. Victaulic reserves the right to change product specifications, designs and standard equipment without notice and without incurring obligations.

Installation

Reference should always be made to the Victaulic installation handbook or installation instructions of the product you are installing. Handbooks are included with each shipment of Victaulic products, providing complete installation and assembly data, and are available in PDF format on our website at www.victaulic.com.

Warranty

Refer to the Warranty section of the current Price List or contact Victaulic for details.

Trademarks

Victaulic and all other Victaulic marks are the trademarks or registered trademarks of Victaulic Company, and/or its affiliated entities, in the U.S. and/or other countries.