

TYPE APPROVAL CERTIFICATE

This is to certify:**That the Pipe Couplings with Bolts Not Covered by a National Standard**with type designation(s)
Style 920 and 920N

Issued to

**Victaulic Company
Easton, PA, USA**

is found to comply with

**DNV GL rules for classification – Ships Pt.4 Ch.6 Piping systems
DNVGL-OS-D101 – Marine and machinery systems and equipment, Edition January 2018
DNV GL class programme DNVGL-CP-0185 – Type approval – Mechanical joints****Application :****Product(s) approved by this certificate is/are accepted for installation on vessels classed by DNV GL.****Temperature range: EPDM: 0°C to +110°C / Nitrile: 0°C to +82°C
Max. working press.: 16 bar
Sizes: See page 2**Issued at **Høvik** on **2018-10-16**for **DNV GL**This Certificate is valid until **2023-06-29**.DNV GL local station: **New York**Approval Engineer: **Iselinn Vindstad****Marianne Spæren Marveng
Head of Section**

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.



Product description

Victaulic Style 920 and 920N Mechanical-T bolted branch outlet and cross assemblies.

Design:

Slip on type coupling comprising of two piece cast housings connected by two bolts for branch connection. The branch connection is available as grooved type or as threaded (size $\leq 2 \frac{1}{2}$ "). The sealing is provided by a rubber gasket, internal to the coupling.

Materials:

Coupling housings: Ductile iron to ASTM A-536 65-45-12
 Bolts and nuts: Carbon steel ASTM A-183
 Gasket: Grade "E" EPDM or Grade "T" Nitrile

Manufacturing locations:

Victaulic Company
 4901 Kesslersville Road,
 Easton, PA 18040 USA

Dalian Bingshan Metal Technology Co., Ltd.
 No.9 Northeastern 7th Street Economic and Technology Development Zone,
 Dalian, Liaoning, 116600, China

Victaulic Polska Sp. z o.o.
 ul. Niepodległości 8
 66-530 Drezdenko, Poland

Sizes:

Nominal Size	Style no.	Nominal Size	Style no.	Nominal Size	Style no.
inches		inches		inches	
2 x 1/2	920N	3 x 1/2	920N	6 x 1 1/4	920N
x 3/4	920N	x 3/4	920N	x 1 1/2	920N
x 1	920N	x 1	920N	x 2	920N
x 1 1/4	920N	x 1 1/4	920N	x 2 1/2	920
x 1 1/2	920N	x 1 1/2	920N	x 76,1mm	920
		x 2	920N	x 3	920
2 1/2 x 1/2	920N			x 4	920
x 3/4	920N	4 x 1/2	920N	159,0mm	920N
x 1	920N	x 3/4	920N	x 1 1/2	
		x 1	920N	x 2	920N
x 1 1/4	920N	x 1 1/4	920N	x 2 1/2	920
x 1 1/2	920N	x 1 1/2	920N	x 4 1/2	920
76,1mm x 1/2	920	x 2	920N	165,1mm x 1	920
x 3/4	920			1/4	
		x 2 1/2	920	x 1 1/2	920
x 1	920	x 76,1mm	920	x 2	920
x 1 1/4	920	x 3	920	x 2 1/2	920
x 1 1/2	920			x 76,1mm	920
		5 x 1 1/2	920	x 3	920
		x 2	920	x 4	920
		x 2 1/2	920		
		x 76,1mm	920		

Application/Limitation

The Victaulic couplings Style 920 and 920N may be used for the following systems:

Systems			Systems		
Flammable fluids (Flash point ≤ 60 °C)			Fresh water		
1	Cargo oil lines	+ 4)	21	Cooling water system	+ 1)
2	Crude oil washing lines	+ 4)	22	Condensate return	+ 1)
3	Vent lines	+ 3)	23	Non-essential system	+
Inert gas			Sanitary/Drains/Scuppers		
4	Water seal effluent lines	+	24	Deck drains (internal)	+ 6)
5	Scrubber effluent lines	+	25	Sanitary drains	+
6	Main lines	+ 2) 4)	26	Scuppers and discharge (overboard)	-
7	Distribution lines	+ 4)	Sounding/ vent		
Flammable fluids (Flash point > 60°C)			27	Water tanks/Dry spaces	+
8	Cargo oil lines	+ 4)	28	Oil tanks (flash point > 60°C)	+ 2) 3)
9	Fuel oil lines	+ 2) 3)			
10	Lubrication oil lines	+ 2) 3)			
11	Hydraulic oil	+ 2) 3)			
12	Thermal oil	+ 2) 3)			
Sea Water			Miscellaneous		
13	Bilge lines	+ 1)	29	Starting/control air	-
14	Sprinkel system	+ 3)	30	Service air (non-essential)	+
15	Foam systems	+ 3)	31	Brine	+
16	Fire main	+ 3)	32	CO ₂ system	-
17	Ballast system	+ 1)	33	Steam	+ 5)
18	Cooling water system	+ 1)			
19	Tank cleaning services	+			
20	Non-essential system	+			

The couplings are permitted for use in systems marked '+', not permitted for systems marked '-'.

Limitations/remarks:

- 1) Inside machinery spaces of category A - only approved fire resistant types.
- 2) Not inside machinery spaces of category A or accommodation spaces. May be accepted in other machinery spaces provided the joints are located in easily visible and accessible positions.
- 3) Approved fire resistant types except in cases where such mechanical joints are installed on exposed open decks, as defined in SOLAS II-2/Reg. 9.2.3.3.2.2(10) and not used for fuel oil lines.
- 4) Only in pump rooms and open decks - only approved fire resistant types.
- 5) May be used for pipes on deck with a design pressure of 10 bar or less.
- 6) Only above bulkhead deck of passenger ships and freeboard deck of cargo ships.

The couplings with Grade E/EPDM gasket are of fire resistant types, and may be used in systems where fire safe application is required.

Threaded end connections of tapered type (NPT/BSPT) may only be used for size ≤ 2" (60.3 mm).

When used in systems where vacuum may occur, precautions shall be taken to prevent the internal gasket from being drawn into the hole.

Materials chosen for the specific system shall be suitable for the intended medium and environmental conditions.

EPDM may not be used for hydrocarbon services.

The couplings are approved to be used in piping systems of class II and III.

Job Id: **262.1-009291-12**
Certificate No: **TAP00001F1**

Type Approval documentation

- Manufacturer's catalogue no. 11.02 "Mechanical-T® Bolted Branch Outlets, STYLES 920 AND 920N", rev. N
- Tightness test and burst pressure test report, File number Ex1820, Issued 11-18-1998
- Report of pressure pulsation test on Style 920/920 N Mechanical T outlet, report number 12-5676-18, 12-5678-19, and 12-5678-20
- Fire Endurance test reports dated 24/2/12 and 23/2/12
- American Bureau of Shipping, miscellaneous survey report PA1979951 dated April 2011

Tests carried out

Tightness test, burst pressure test, fire test, pressure pulsation test, vacuum test

Certification

Material certification shall follow DNVGL-RU-SHIP Pt. 4 Ch. 6 Sec. 2 Table 3.

Marking of product

For traceability to this type approval, the couplings are at least to be marked with:

- manufacturer's name or trade mark
- type designation
- size

Periodical assessment

For retention of the Type Approval, a DNV GL Surveyor shall perform periodical assessment after two years (+/- 90 days) and after 3.5 years (+/- 90 days) to verify that the conditions for the approval are complied with. Reference is made to DNVGL-CP-0338.